



IM-23G

IM-23G SERIES

Indoor Ice Merchandiser

MODEL
 IM-23G

FEATURES

STANDARD ELECTRONIC CONTROL

- Displays temperature
- Fan working indicator
- Door open alarm that sounds after door is open more than 30 seconds
- Easily adjusted temperature settings



CONSTRUCTION

- Two-inch thick foamed-in-place "low ODP" urethane insulation
- Interior fluorescent light
- Lighted promotional graphic panel
- Adjustable leveling legs
- Independent on/off switch
- Rear wall guard for efficient air circulation
- Heavy-duty epoxy-coated welded wire bottom shelf

FINISH

- White epoxy polyester exterior finish (powder coated)
- Stainless steel top and bottom on interior
- Interior sides and back coated with white PVC laminate

DOOR

- Auto-close, triple pane, heated glass door with hold-open feature

- Door size: 27" x 55"
- White door frame
- Replaceable gaskets

REFRIGERATION

- Refrigerant: R-404A
- Self-contained, bottom mounted, factory tested refrigeration system
- Slide-out system for easy access
- Top mounted, low profile interior fan housing
- Temperature range: 5° to -15°F (-18° to -26°C)
- R-factor (insulation efficiency rating): 16.67

WARRANTY

- Standard limited four year extended compressor and one year limited parts and labor




IM-23G SERIES

INDOOR ICE MERCHANDISER

TECHNICAL SPECIFICATIONS

MODEL	DIMENSIONS (in.)			DIMENSIONS (mm)			VOLTS	AMPS	UNIT H.P.	CAPACITY 8 LB. BAGS	CAPACITY CU. FT.	SHIP CU. FT.	SHIP WT. (LB/KG)
	L	D	H	L	D	H							
IM-23G	27	31	76 ⁷ / ₈	686	787	1953	115	8.2	3/4	43	23.0	48.5	400/182




LISTINGS



California Energy Commission Certified

HOOKUP

Via plug in 5 ft. long, flexible 14/3 cord with molded plug.



NEMA 5-15P

BID SPECIFICATIONS

Item no. IM-23G.

Provide _____ () Indoor Ice Merchandiser(s), Master-Bilt model no. IM-23G.

Merchandiser will be equipped with a standard electronic controller system with monitoring and alarm functions.

Doors will feature triple pane glass. They will also be heated and will have auto-close and hold-open features as well as replaceable gaskets.

Construction will consist of two-inch

thick foamed-in-place "low ODP" urethane insulated walls. Cabinet interior top and bottom constructed of stainless steel. A heavy-duty epoxy-coated welded wire bottom shelf will also be provided.

Merchandiser will contain an interior fluorescent light and a and a fluorescent-lit promotional graphic panel. Other standard features will include adjustable leveling legs, an independent on/off switch and a rear wall guard for efficient air circulation.

The refrigeration system will be self-con-

tained, bottom mounted and factory tested. The system will also be a slide-out type for easy access. Refrigerant type will be R-404A. Temperature range will be 5° to -15°F (-18° to -26°C)

Merchandiser to have standard limited four year extended compressor warranty and one year limited parts and labor warranty.

Merchandiser to be UL, C-UL and NSF listed also California Energy Commission certified.

NOTE: Cabinet designed for optimum performance in air-conditioned area at 75°F ambient and 55% relative humidity. All specifications subject to change without notice.



908 Highway 15 North • New Albany, MS 38652

PHONE: 800-647-1284 or 662-534-9061 • FAX: 800-232-3966 or 662-534-6049 • www.master-bilt.com

